

DATASHEET

19" Network Cabinet 42U 800x1000, IP55, with Pre-Assembled Plinth, RAL9005



General data

19" Network cabinet according to DIN 41494

Steel sheet housing with welded frame, completely pre-assembled

Pre-assembled plinth 100 mm

Inside front and rear 4 x 19" profiles (2 front, 2 rear-sided), galvanised, depth-adjustable in 25 mm raster

Numbering of rack units at the 19" profiles

Front and rear door steel, 1-part

Front and rear door with 3-point locking with turning handle, lockable

Door opening angle front and rear > 120°

Side walls not detachable

Inner roof pre-punched openings for fan units

Bottom prepared with air inlet filters and rubber grommets Ø 80 mm for cable entry

This datasheet was created automatically on 27-12-2022 . Technical changes reserved.

DATASHEET

19" Network Cabinet 42U 800x1000, IP55, with Pre-Assembled Plinth, RAL9005

Internal earthing of all cabinet sections

Max. load 1000 kg

Paint finish RAL9005, jet black

Protection degree IP55

Included accessories: 1 x set of captive nuts (PU 20 pcs.), pre-installed plinth, 2 x key

Delivery in transport packaging on disposable pallet

Allgemeine Daten	
With socket	True
Modular spacing	482.6 mm (19 inch)
With front door	True
Type of back door	Steel door 1-part
Type of ventilation	Passive
With backside door	True
Surface finishing	Powder coating
With roof plate	True
Degree of protection (IP)	IP55
Type of front door	Steel door 1-part
With sidewall	True
Mounting level	Front and rear
Model	With permanent frame
With earthing	True
Material	steel
Demountable	False

Available variants									
ArtNr.	Bezeichnung	Colour	Depth	Number of height units	Width	Höhe	RAL-Nummer	Anzahl der Türen	Geeignete Lüfter
692442	19" Network Cabinet 42U 800x1000, IP55, with Pre-Assembled Plinth, RAL9005	black	1000 mm	42 U	800 mm	2160 mm	9005	2	2/4/6-fach

This datasheet was created automatically on 27-12-2022 . Technical changes reserved.