

DATASHEET

19" Network Cabinet 42U 600x600, IP55, with Pre-Assembled Plinth, RAL9005



General data

19" Network cabinet according to DIN 41494
Steel sheet housing with welded frame, completely pre-assembled
Pre-assembled plinth 100 mm
Inside front and rear 4 x 19" profiles (2 front, 2 rear-sided), galvanised, depth-adjustable in 25 mm raster
Numbering of rack units at the 19" profiles
Front and rear door steel, 1-part
Front and rear door with 3-point locking with turning handle, lockable

Door opening angle front and rear > 120°
Side walls not detachable
Inner roof pre-punched openings for fan units
Bottom prepared with air inlet filters and rubber grommets Ø 80 mm for cable entry

This datasheet was created automatically on 27-12-2022 . Technical changes reserved.

DATASHEET

19" Network Cabinet 42U 600x600, IP55, with Pre-Assembled Plinth, RAL9005

Internal earthing of all cabinet sections

Max. load 1000 kg

Paint finish RAL9005, jet black

Protection degree IP55

Included accessories: 1 x set of captive nuts (PU 20 pcs.), pre-installed plinth, 2 x key

Delivery in transport packaging on disposable pallet

Allgemeine Daten	
With socket	True
Modular spacing	482.6 mm (19 inch)
With front door	True
Type of back door	Steel door 1-part
Type of ventilation	Passive
With backside door	True
Surface finishing	Powder coating
With roof plate	True
Degree of protection (IP)	IP55
Type of front door	Steel door 1-part
With sidewall	True
Mounting level	Front and rear
Model	With permanent frame
With earthing	True
Material	steel
Demountable	False

Available variants									
ArtNr.	Bezeichnung	Colour	Depth	Number of height units	Width	Höhe	RAL-Nummer	Anzahl der Türen	Geeignete Lüfter
692524	19" Network Cabinet 42U 600x600, IP55, with Pre-Assembled Plinth, RAL9005	black	600 mm	24 U	600 mm	1360 mm	9005	2	nur 2-fach

This datasheet was created automatically on 27-12-2022 . Technical changes reserved.