

DATASHEET

10" Wall Housing 4U, Depth 300 mm, RAL9005



General data

Self-ventilated steel sheet housing, welded
 Front door lockable, with latch, door opening angle > 180°
 Front door with window made of certified safety glass (4 mm)
 2 x 10" profile rails, depth adjustable, usable mounting depth 203..263 mm
 Cable entry possible from top, bottom (opening 44 x 115 mm) or rear-sided (177 x 280 mm)
 Bottom with 4 x thread for leveling feet M8 (Art.-No. OFF-NIV01)
 Roof with pre-punched opening for single fan
 Long holes for wall mounting
 Max. load 60 kg
 Paint finish RAL7035, light grey / RAL9005 jet black
 Delivery in transport packaging, incl. 2 x brush, 2 x key

Allgemeine Daten

This datasheet was created automatically on 27-12-2022 . Technical changes reserved.

DATASHEET

10" Wall Housing 4U, Depth 300 mm, RAL9005

With front door	True
Type of ventilation	Passive
Demountable	True
Surface finishing	powder coating
Number of cartons	1
With roof plate	True
Mounting level	Front side
With sidewall	True
Model	With permanent frame
With earthing	True
Number of doors	1
Material	steel
Degree of protection (IP)	IP20
Type of profile rail	L-shaped
Modular spacing	254 mm (10 inch)

Available variants

ArtNr.	Bezeichnung	Colour	Depth	Height	Max. Load	Number of height units	Width	RAL-Nummer
691803-4G	10" Wall Housing 4U, Depth 300 mm, RAL7035	grey	300 mm	234 mm	60 kg	4 U	300 mm	7035
691803-6G	10" Wall Housing 6U, Depth 300 mm, RAL7035	grey	300 mm	322 mm	60 kg	6 U	300 mm	7035
691803-9N	10" Wall Housing 9U, Depth 300 mm, RAL7035	grey	300 mm	455 mm	60 kg	9 U	300 mm	7035
691803-4N	10" Wall Housing 4U, Depth 300 mm, RAL9005	black	300 mm	234 mm	60 kg	4 U	300 mm	9005
691803-6N	10" Wall Housing 6U, Depth 300 mm, RAL9005	black	300 mm	322 mm	60 kg	6 U	300 mm	9005
691803-9N	10" Wall Housing 9U, Depth 300 mm, RAL9005	black	300 mm	455 mm	60 kg	9 U	300 mm	9005

This datasheet was created automatically on 27-12-2022 . Technical changes reserved.