

DATASHEET

19" Wall Housing IP55, 16U, Glass Door, Depth 450 mm, RAL7035



General data

Steel sheet housing with welded corpus, completely pre-assembled

Right- and left-sided metal covered air inlets for passive ventilation

Side walls not detachable

Roof hinged, inner roof prepared for mounting of Plug&Play fan unit Art.-No. 691656GR (cable not included, please order separately, e.g. Art.-No. EK504.x)

Bottom with PG glands 1 x PG48, 2 x PG21 and 3 x Ø 20 mm PVC blind grommets

For depth 450 mm inside 2 x 19" profile rails front-sided, galvanised, with numbering of rack units (U)

For depth 600 mm inside 4 x 19" profile rails (2 front, 2 rear), galvanised, with numbering of rack units (U)

Front door with window of certified safety glass and 3-point bar locking, lockable, with profile half-cylinder acc. to DIN 18252 / EN1303

Profile half-cylinder exchangeable by customer

Cabinet parts inside completely earthed

Max. load 100 kg

Paint finish RAL7035, light grey

Protection degree IP55

Plinth for use as standing cabinet available as option

Included accessories: 4 x Wall mount angle, 2 x key

DATASHEET

19" Wall Housing IP55, 16U, Glass Door, Depth 450 mm, RAL7035

Allgemeine Daten

Modular spacing	482.6 mm (19 inch)
With front door	True
Type of ventilation	Passive
Demountable	True
Surface finishing	powder coating
Number of cartons	1
With roof plate	True
Degree of protection (IP)	IP55
Mounting level	Front side
With sidewall	True
Model	With permanent frame
With earthing	True
Number of doors	1
Material	steel
Type of profile rail	L-shaped

Available variants

ArtNr.	Bezeichnung	Colour	Depth	Height	Max. Load	Number of height units	Width	RAL-Nummer
691707-45-1	19" Wall Housing IP55, 7U, Glass Door, Depth 450 mm, RAL7035	grey	450 mm	410 mm	100 kg	7 U	600 mm	7035
691709-45-1	19" Wall Housing IP55, 9U, Glass Door, Depth 450 mm, RAL7035	grey	450 mm	500 mm	100 kg	9 U	600 mm	7035
691712-45-1	19" Wall Housing IP55, 12U, Glass Door, Depth 450 mm, RAL7035	grey	450 mm	630 mm	100 kg	12 U	600 mm	7035
691716-45-1	19" Wall Housing IP55, 16U, Glass Door, Depth 450 mm, RAL7035	grey	450 mm	810 mm	100 kg	16 U	600 mm	7035
691720-45-1	19" Wall Housing IP55, 20U, Glass Door, Depth 450 mm, RAL7035	grey	450 mm	1000 mm	100 kg	20 U	600 mm	7035