

DATASHEET

19" Co-Location Racks PRO, 800 x 800 mm



Description

19" network cabinet according to DIN 41494

Steel sheet housing with screwed frame, completely pre-assembled, self-ventilated

1, 2, 3 or 4 boxes for individual access

Every box with independent cable ducts left and right for cable entry from top or bottom

Inside front and rear 4 x 19" profiles per box (2 front, 2 rear), galvanised, step-less depth-adjustable

Numbering of height units at the profiles

Front- and rear doors steel, perforated, 1-part

Doors with 1-point turning handle, lockable, incl. profile half-cylinder acc. to DIN 18252 / EN 1303

Profile half-cylinder exchangeable by customer (30/10 mm)

Door stop left and right-sided possible

Detachable side walls with 2 x latch locking (lock equal to door lock)

Side walls optional available perforated

Cabinets stackable side-by-side with and without side wall via baying set PRO-ANR01

Roof and bottom with covered cutouts for cable entry (left/right) and for accommodation of fan unit PRO-LFD02BO.xx

Intermediate bottoms sealed to side walls

Internal earthing of all cabinet parts

Max. load 600 kg

Paint finish RAL7035, light grey / RAL9005, jet black

Protection degree IP20

Included accessories: 1 x set of captive nuts (PU 20 pcs.), 4 x Leveling feet M12, 2 x key

Delivery in transport packaging on disposable pallet

DATASHEET

19" Co-Location Racks PRO, 800 x 800 mm

General data

Type of front door	Steel perforated 1-part
Type of back door	Steel perforated 1-part
Mounting level	Front and rear
Model	With permanent frame
Modular spacing	482,6 mm (19 inch)
Type of profile rail	Crank
Type of ventilation	Passive
With roof plate	True
With earthing	True
With front door	True
With backside door	True
With sidewall	True
With socket	False
Material	Steel
Surface finishing	With powder coating
Degree of protection (IP)	IP20
Demountable	True

Available variants

Article no.	Title	Width	Depth	Number of height units	Colour of	Number of Boxes	Number of doors	Height	Suitable Fans	RAL-number	Max. load capacity	Material front door	Front door locking system	Material rear door	Rear door locking system	With vertical cable management
PRO-CL1-4288TS.P1	Co-Location Rack PRO, 1 x 42U, 800x800 mm, F+R 1-Part Perforated, RAL9005	800 mm	800 mm	1 x 42 U	Black	1	2	1963 mm	PRO-LFD02BO.xx	9005	600 kg	Steel	One point	Steel	One point	True
BAIECO-42-80-80	Co-Location Rack PRO, 2 x 20U, 800x800 mm, F+R 1-Part Perforated, RAL9005	800 mm	800 mm	2 x 20 U	Black	2	4	1963 mm	PRO-LFD02BO.xx	9005	600 kg	Steel	One point	Steel	One point	True
BAIECO-42-80-80-4	Co-Location Rack PRO, 4 x 9U, 800x800 mm, F+R 1-Part Perforated, RAL9005	800 mm	800 mm	4 x 9 U	Black	4	8	1963 mm	PRO-LFD02BO.xx	9005	600 kg	Steel	One point	Steel	One point	True