



DATASHEET

19" Roll Container 15U, 600 x 800 mm, Acoustically Insulated, Office Design



General data

19" Network cabinet acc. to DIN41494 as roll container or undercounter housing for office environments
 High-quality acoustical insulated variant for ergonomic work, suitable for installation directly at the working place
 Attractive, stable MDF plate at the upper side enables parking of further devices (printer etc.) on the cabinet
 Use of sound insulation mats in studio technology in thickness 20, 40 und 50 mm, equal to the acoustical problem zones in cabinets
 Attenuation (typ.) 8 .. 25 dB (frequency-dependent)
 Especially decoupled, smooth running "Silent" fans at the rear wall guide the heat to outside, converted air volume 294 m³/h
 Fresh air feeding from bottom-front via filter grid
 Cable entry rear-sided below via sound bridge and brush
 Inside 4 x 19" rails (2 front, 2 rear), depth-adjustable in 25 mm raster
 Front door with window of certified safety glass (5 mm), 1-part, with turning handle and profile half-cylinder acc. to DIN18252, PHC exchangeable by customer
 Rear door with 1 x latch, lock equal to door lock
 Side walls detachable with 2 x latch, lock equal to door lock
 Max. load 300 kg (castors) / 600 kg (leveling feet)
 Dimensions (W x D x H) 600 x 800 x 900 mm
 Paint finish und MDF plate RAL7035, light grey

This datasheet was created automatically on 27-12-2022 . Technical changes reserved.

DATASHEET

19" Roll Container 15U, 600 x 800 mm, Acoustically Insulated, Office Design

Delivery incl. set of 4 castors (2 with brake), 2 x key, 1 x power supply for fans

All EFB housings are available as acoustical insulated type and in individual design - ask your sales contact!

Allgemeine Daten	
With front door	True
Demountable	True
Surface finishing	powder coating
Number of cartons	1
With roof plate	True
Degree of protection (IP)	other
Type of ventilation	Active
Modular spacing	482,6 mm (19 inch)
With sidewall	True
Mounting level	Front and rear
Model	With permanent frame
With earthing	True
Material	steel
Number of doors	2
Type of profile rail	Crank

Available variants								
ArtNr.	Bezeichnung	Colour	Depth	Height	Max. Load	Number of height units	Width	RAL-Nummer
692615	19" Roll Container 15U, 600 x 800 mm, Acoustically Insulated, Office Design	grey	800 mm	900 mm	600 kg	15 U	600 mm	7035

This datasheet was created automatically on 27-12-2022 . Technical changes reserved.